



Adapted for
SDS-MAX bits

Excellent performance equivalent to AC Model

BRUSHLESS
X2
18V + 18V → 36V

Newly developed BL motor
delivers high power



Drilling work amount

Work volume on a single full battery charge

About **25** holes

- ◆ w/ T.C.T. bit 11/16"
- ◆ Depth : 5-1/2"
- ◆ Concrete Compressive Strength: 5,800 PSI
- ◆ Battery : BL1850Bx2

Demolition work

with bull point

Impact Energy

[EPTA-Procedure 05/2009]

8.0J

Makita HR4013C 8.0J

AVT & SOFT
NO LOAD

ANTI VIBRATION TECHNOLOGY

Vibration absorbing
housing isolates handle
and motor.

Active dynamic vibration
absorber moves in the
opposite direction to the
drive piston to reduce
vibration.

Damper spring absorbs
impact vibrations from
the drill bit.



AWS

Auto-start Wireless System



Wireless unit

Part No.
198901-5

Bluetooth®

Switch on the tool
Vacuum cleaner is activated



DVC864

■ Comparison of Vibration level* and Time to reach ELV
(Exposure Limit of Vibration)**

* It is known as the tri-axial value and value at
Directive of A(8).

**It means the maximum amount of vibration that an
operator may be exposed to on any single day.

Time to reach ELV (min)	100	200	550	
Makita DHR400	5.0m/s ²		540min	
Makita HR4013C	5.0m/s ²		540min	
Vibration level (m/s ²)	0	5	10	15

**AWS connects to power tool
via Bluetooth.**

Wireless unit



Bluetooth®

The Bluetooth® word mark and logos are registered trademarks owned
by the Bluetooth SIG, Inc. and any use of such marks by Makita is under
license. Other trademarks and trade names are those of their respective
owners.

Expand AWS Line-up

AWS

