

Accessories

New nylon cord for better cutting efficiency

The new nylon cord features more sharpness, about 10% less noise, and about 15% less power consumption compared with the current one.

The new spiral cord with four-leaf clover-like cross section, of our own design, has been developed based on our advanced technology and by reviewing the material, the hardness and the shape of cross section of the current 2 mm diameter cord with circular cross section.

B&F Eco4
Part No. 197297-1 (M8x1.25 RH)

Four-leaf clover-like cross section (ø 2.0mm)



Size
2.0 mm x 15 m Part No.
197472-9



Spiral cord body

18V
Lithium-ion
LXT

Powered by two 18V Li-Ion batteries in series

5.0Ah BL1850 4.0Ah BL1840 3.0Ah BL1830
2.0Ah BL1820 1.5Ah BL1815H

140+ TOOLS

Expand Your Lithium Line Up

Product availability and specifications may vary by country or area.

18Vx2 LXT 14" Cordless Line Trimmer		DUR364LZ
Brake	Electronic 2-Speed (DUR364L)	Battery Two 18V Li-Ion
Reversing	Constant Speed	Cutting Width 13-3/4" (350 mm)
Soft Start		No Load Speed Low: 5,000 RPM / High: 6,500 RPM
		Overall Length 69" (1,754 mm)

When QUALITY & SERVICE COUNT – Choose Makita

makita.ca

Satisfy Professional's Needs



18Vx2 LXT 14" Cordless Line Trimmer DUR364LZ



Photo : DUR365U
Not Available In Canada

BL
MOTOR

18Vx2
36V

High power and more work amount thanks to New Brushless motor

Low noise

Sound power level
89dB(A) (nylon)
DUR364LZ



The best choices for use in Resorts, Public Places and Among Residential Areas.



High work efficiency

achieved by placing the motor on the blade side of motor housing to realize direct drive system.



Powered by two 18V Li-ion batteries in series



Two 18V Li-ion batteries can be directly installed on the machine to supply energy to the powerful 36V DC motor drive system.

Continuous use (min) (Two 18V Li-ion batteries)		BL1815N (1.5 Ah)	BL1830 (3.0 Ah)	BL1840 (4.0 Ah)	BL1850 (5.0 Ah)
DUR364LZ with Nylon cord (in no load)	Low	30	55	75	100
	High	15	28	35	45
Charging time DC18RD		15	22	36	45



XPT EXTREME PROTECTION TECHNOLOGY

Extreme Protection Technology

For use in outdoor applications or harsh environments, protection from dust and dripping water is enhanced.

Dual battery fuel gauge

indicates the power remaining in each battery individually in 3 stages with 3 LEDs.

Constant speed control

- minimizes reduction in rotation speed under load, increasing operation efficiency.
- Lowers noise under no load.

(Power increase can be felt compared with the current model, because the rotation speed is maintained during operation even when no load speed is lowered.)



Speed mode
DUR364LZ : Electronic 2-speed

Power switch

- Can be turned ON and OFF by pressing and holding down the button.
- Speed mode can be changed by simply pushing the button.
- Automatically turned off by no operation in 1 minute.

Reverse switch

Reverse switch for easy removal of grass clippings from the cutting tool

- Grass clippings can be removed by slow reverse rotation of the cutting tool (automatically stops in 3 seconds) by pressing Touch button switch and pulling Trigger switch.
- The motor can automatically return to forward rotation after the 3-second reverse rotation, saving time pushing a button for forward rotation.



DUR364L

350mm nylon cutting head rotating clockwise

Nylon cutting head and plastic blade (Optional accessory) can be attached.



Prevents grass clippings from flying towards user's side.

Also can be used as an edger



Soft grip

Electronic 2-Speed



Aluminum motor housing

Smaller protector for better view of cutting area
Compact protector for nylon cutting head provides better view of the blade tips, without losing the performance for prevention of scattering of grass clippings.