



11/16" Rotary Hammers
HR1841F / HR1840

Satisfy Professional's Needs



SDS-PLUS Shank

Compact & Low vibration



AVT

ANTI VIBRATION TECHNOLOGY

(HR1841F only)

photo : HR1841F

Vibration value

46% decrease


Compared to our current models

Excellent drilling performance



Feature

2 operation modes



One-touch sliding chuck for easy bit change



LED job light
(HR1841F only)



Accessories

Dust cup
Part.No : 198362-9



Grip base set
Part.No : 194581-5



11/16" Rotary Hammers

HR1841F / HR1840 11/16" (18 mm) Adapted for SDS-PLUS bits

- Double Insulation
- Variable Speed
- Reversing
- SDS-PLUS Shank
- Torque Limiter
- Dust Collection
- Built-in Job Light (HR1841F only)
- Carrying Case

	HR1841F	HR1840
Bit Type	SDS-PLUS	SDS-PLUS
Maximum Capacities:	Concrete: 11/16" (18 mm) Steel: 1/2" (13 mm) Wood: 15/16" (24 mm)	Concrete: 11/16" (18 mm) Steel: 1/2" (13 mm) Wood: 15/16" (24 mm)
No Load Speed	0 - 2,100 RPM	0 - 2,100 RPM
Blows Per Minute	0 - 4,800 BPM	0 - 4,800 BPM
Impact Energy	1.4 J (1.0 ft. lbs)	1.4 J (1.0 ft. lbs)
AMPS (120V)	4.1 A	4.1 A
Vibration Level	7.5 m/s ² (Concrete) / 3.0 m/s ² (Metal)	7.5 m/s ² (Concrete) / 3.0 m/s ² (Metal)
Overall Length	11-1/4" (285 mm)	11-1/4" (285 mm)

HR1841F Standard Equipment: Side Handle (158057-6),
Depth Gauge (415486-9), Plastic Carrying Case (824650-5)

HR1840 Standard Equipment: Side Handle (158057-6),
Depth Gauge (415486-9), Plastic Carrying Case (821706-5)

When QUALITY & SERVICE COUNTS – Choose Makita

makita.ca