



CORDLESS THIN KERF CUTTING SOLUTIONS

Cut-Off Wheel Meule à tronçonner Disco de Recorte

B-46165

5" x 0.032" x 7/8" (125 x 0.8 x 22.23mm)

12,250 RPM TR/MIN MAXIMUM SPEED

Thakite

5"x0.032"

e as directed ANSI safety code B7.1 & O

Fast Cutti

Makita Corporation Anjo, Aichi, Japan

INNOVATION & TECHNOLOGY

CUTTING

RELATE

RELATED ACCESSORIES

INNOVATION & TECHNOLOGY



- Cuts up to 37% FASTIER
- Up to 20% MORE cuts per charge
- · Reduced material waste with no burring
- Reduced swarf limits contamination of work area
- Thin design limits friction and heat buildup
- Ideal for cutting threaded rod, rebar, thin gauge material, HVAC ducting and more







The test results depend to a great extent on the hardness of materials, etc.

2. The numbers in the bar graphs are relative values when the capacity of Makita Cut-off wheel (Thickness 0.045") is indexed at 100.

INNOVATION & TECHNOLOGY

CUTTING SOLUTIONS RELATED TOOLS RELATED ACCESSORIES

CUTTING SOLUTIONS



INNOVATION & TECHNOLOGY

CUTTING SOLUTIONS RELATED TOOLS RELATED ACCESSORIES

RELATED TOOLS

18V Li-Ion Angle Grinder

4-1/2" Thumb Switch - DGA452Z



18V Li-Ion Brushless Angle Grinders

4-1/2" Paddle Switch - DGA455Z 5" Paddle Switch - DGA505Z



Product Demo / Job site Call Schedule to have a product specialist visit your site

4-1/2"

Also Available 18V Li-lon Brushless Angle Grinders 4-1/2" Thumb Switch - DGA454Z 5" Thumb Switch - DGA504Z

RELATED TOOLS

RELATED ACCESSORIES

Thin Kerf Cut Off Wheel Guards

18V Grinder	Wheel Guard
DGA452Z	135103-2
DGA454Z / DGA455Z	122910-2
DGA504Z / DGA505Z	122911-0

Professional Work Gloves

Size	Construction	Impact	Demolition
Medium	MK403-M	MK404-M	MK405-M
Large	MK403-L	MK404-L	MK405-L
XL	MK403-XL	MK404-XL	MK405-XL









ALWAYS ensure tool is properly guarded. Refer to operator's manual for more information



Anti-Vibration Side Handle

INNOVATION &

CUTTING

RELATED

RELATED ACCESSORIES